

# Fringed Vest - Cleckheaton

## MATERIALS:

Cleckheaton Machinewash 8 ply crepe ....  
 No. 8 (4.00 m.m.) and No. 9 (3.50 m.m.) crochet hooks or  
 THE SIZE REQUIRED TO GIVE THE CORRECT TENSION

SIZES	10	12	14
balls	4	4	5

**MEASUREMENT:** Length from shoulder

inches	16	16 <sup>1/2</sup>	17
cm	40.5	42	43

**TENSION:** 1 patt. to 1 in. No. 8 hook.

## ABBREVIATIONS:

Y.o.h. = Yarn over hook.  
 L.tr. = Long treble. Y.o.h. twice and draw yarn through  
 ch space about half inch long. Y.o.h. and draw yarn  
 through the first two loops. Y.o.h. and draw yarn through  
 the next two loops. Y.o.h. and draw yarn through the last  
 two loops.

*If you need help with your pattern,  
 please phone (03) 9380 3888  
 or Toll Free 1800 337 032  
 and quote Z186*

**PATTERN** = 3 L.tr. in one space.

## FRONT & BACK (Worked in one piece to armholes):

Using No. 8 hook make ..... ch 178 **188** 198  
**1st row:** Make 3 L.tr. (Pattern) in the 9th ch from hook. \* 1 ch, miss 4 ch,  
 3 L.tr. in next ch. Repeat from \* until .....  
 patterns are made, then 1 L.tr. in last ch for edge, turn.  
**2nd row:** 5 ch firmly, 3 L.tr. in between the previous L.tr. and the first pattern  
 \* 1 ch, 3 L.tr. between previous first and second patterns. Repeat from \* until .....  
 patterns are made. 1 ch, 1 L.tr. on top of the last ch. Repeat 2nd row until  
 work meas. 9 ins. Fasten off. Divide armholes as follows:—  
 Size 10— two fronts each 8<sup>1/2</sup> patts.  
**Size 12 — two fronts each 9 patts.**  
 Size 14 — two fronts each 9<sup>1/2</sup> patts.  
 (Use marker at the division point.)

## BACK:

**1st row:** Join yarn at the division point. Sl. st over ..... patts. 1<sup>1/2</sup> **2** 2<sup>1/2</sup>  
 and also over the next one ch space. 5 ch firmly. 3 L.tr. between next two  
 patts. Continue in pattern until..... patts. 13 **13** 13  
 are made. 1 L.tr. between next two patterns, turn.  
**2nd row:** 5 ch firmly, 3 L.tr. between previous L.tr. and first pattern. Continue  
 patterns as before until..... patts. 13 **13** 13  
 are made, 1 ch, 1 L.tr. in last ch. Repeat 2nd row until ... rows 9 **10** 11  
 or □ inches 7 **7<sup>1/2</sup>** 8  
 are made. Shape shoulder as follows:— or cm 18 **19** 20  
 Sl. st over one pattern, 1 ch, 3 d.c. between next two patterns. 1 Ch, 3 tr. between next patterns,  
 1 ch, 3 L.tr. between next patterns. Continue in pattern to last 3 patt. 3 tr. between next patterns,  
 1 ch, 3 d.c. between next patterns, sl. st to end. Fasten off.

## FRONTS:

**Shape armholes as back.** Keep armhole edge straight and firm **at the same time**  
 decrease one pattern at front edge every alternate row by omitting the first  
 pattern. Cont. dec. until 3 patterns remain. Continue these 3 patterns until  
 armhole rows correspond with the back. Then shape shoulder in the same  
 manner as back. Fasten off.

**TO MAKE UP:** Join shoulders with flat seam. Use No. 9 hook make two rounds of  
 d.c. around body and armholes. Make a row of 5 in. fringe along the hemline every  
 3rd d.c. in 3 strands doubled. Press lightly with warm iron and damp cloth. Make chain  
 of double yarn and attach at front if desired.

